

# exported resources cheat sheet

## mysql

```
[master]
storeconfigs = true
dbadapter = mysql
dbuser = puppet
dbpassword = supersecret
dbserver = localhost
dbsocket = /var/lib/mysql/mysql.sock
```

## sqlite

```
[master]
storeconfigs = true
dbadapter = sqlite3
```

## stored configurations (required)

## TAGS

```
class a {
  @@file {"exported_{$::hostname}":
    content => "$::hostname\n"
    tag      => "hostname"
  }
  class b {
    @@file {"exported_${::fqdn}":
      content => "${::fqdn}\n"
      tag      => "fqdn"
    }
  File <<| tag == 'hostname' |>>
  File <<| tag == 'fqdn' |>>
}
```

```
realize(File["virtual"])
```

```
}
```

## Virtualizing Resources

Keeps the resource local to this node.

## Export a resource

```
@@file {"exported_${::hostname}":
  path      => "/path/to/files/${::hostname}",
  content   => "${::hostname}\n",
  mode      => 0640
}
```

*Resource titles must be unique, appending the \${::hostname} to the title ensures the resource will be unique.*

## Collecting a resource

```
File <<| |>>
```

*To override exported resource settings upon collection or interact with local-only objects*

```
File <<| |>> {
  mode => 0644,
  notify => Service["onlyinthismanifest"]
}
```